

Spur Gearheads

0,1 Nm

For combination with
DC-Micromotors
Brushless DC-Motors
Stepper Motors

Series 15/5 S



	15/5 S
Housing material	metal
Geartrain material	steel
Recommended max. input speed for: – continuous operation	5 000 rpm
Backlash, at no-load	≤ 3 °
Bearings on output shaft	ball bearings, preloaded
Shaft load, max.:	
– radial (6,5 mm from mounting face)	≤ 25 N
– axial	≤ 5 N
Shaft press fit force, max.	≤ 5 N
Shaft play	
– radial (6,5 mm from mounting face)	≤ 0,02 mm
– axial	= 0 mm
Operating temperature range	- 30 ... + 100 °C

Specifications

	2	3	4	4	5	5	6	6	7
Number of gear stages									
Continuous torque	mNm 60	60	100	100	100	100	100	100	100
Intermittent torque	mNm 150	150	300	150	300	150	300	150	300
Weight without motor, ca.	g 17	19	21	21	22	22	24	24	25
Efficiency, max.	% 81	73	66	66	59	59	53	53	48
Direction of rotation, drive to output	=	≠	=	=	≠	≠	=	=	≠
Reduction ratio ¹⁾ (rounded)	6,3:1 11,8:1	22:1 41:1	76:1	141:1	262:1	485:1	900:1	1 670:1	3 101:1
L2 [mm] = length without motor	26,2	29,9	32,0	32,0	34,1	34,1	36,2	36,2	38,3
L1 [mm] = length with motor									
1319E...SR	32,5	36,2	38,3	38,3	40,4	40,4	42,5	42,5	44,6
1331E...SR	44,5	48,2	50,3	50,3	52,4	52,4	54,5	54,5	56,6
1516E...S	29,1	32,8	34,9	34,9	37,0	37,0	39,1	39,1	41,2
1516E...SR	29,1	32,8	34,9	34,9	37,0	37,0	39,1	39,1	41,2
1524E...SR	37,1	40,8	42,9	42,9	45,0	45,0	47,1	47,1	49,2
1524E...BSL	37,5	41,2	43,3	43,3	45,4	45,4	47,5	47,5	49,6
1536E...BSL	49,9	53,6	55,7	55,7	57,8	57,8	59,9	59,9	62,0
AM1524...-57	30,0	33,7	35,8	35,8	37,9	37,9	40,0	40,0	42,1

¹⁾ The reduction ratios are rounded, the exact values are available on request or at www.faulhaber.com.

Note: The gearheads as S-type have all steel gears and heavy duty lubricant for extended lifetime performance.



Spur Gearheads

0,1 Nm

For combination with
DC-Micromotors
Brushless DC-Motors
Stepper Motors

Series 15/5 S

	15/5 S
Housing material	metal
Geartrain material	steel
Recommended max. input speed for:	
– continuous operation	5 000 rpm
Backlash, at no-load	≤ 3 °
Bearings on output shaft	ball bearings, preloaded
Shaft load, max.:	
– radial (6,5 mm from mounting face)	≤ 25 N
– axial	≤ 5 N
Shaft press fit force, max.	≤ 5 N
Shaft play	
– radial (6,5 mm from mounting face)	≤ 0,02 mm
– axial	= 0 mm
Operating temperature range	- 30 ... + 100 °C

Specifications		7	8	8	9	9	10	10
Number of gear stages								
Continuous torque	mNm	100	100	100	100	100	100	100
Intermittent torque	mNm	150	300	150	300	150	300	150
Weight without motor, ca.	g	25	26	26	28	28	30	30
Efficiency, max.	%	48	43	43	39	39	35	35
Direction of rotation, drive to output		≠	=	=	≠	≠	=	=
Reduction ratio ¹⁾ (rounded)		5 752:1	10 683:1	19 813:1	36 796:1	68 245:1	126 741:1	235 067:1
L2 [mm] = length without motor		38,3	40,4	40,4	42,5	42,5	44,6	44,6
L1 [mm] = length with motor								
	1319E...SR	44,6	46,7	46,7	48,8	48,8	50,9	50,9
	1331E...SR	56,6	58,7	58,7	60,8	60,8	62,9	62,9
	1516E...S	41,2	43,3	43,3	45,4	45,4	47,5	47,5
	1516E...SR	41,2	43,3	43,3	45,4	45,4	47,5	47,5
	1524E...SR	49,2	51,3	51,3	53,4	53,4	55,5	55,5
	1524E...BSL	49,6	51,7	51,7	53,8	53,8	55,9	55,9
	1536E...BSL	62,0	64,1	64,1	66,2	66,2	68,3	68,3
	AM1524...-57	42,1	44,2	44,2	46,3	46,3	48,4	48,4

¹⁾ The reduction ratios are rounded, the exact values are available on request or at www.faulhaber.com.

Note: The gearheads as S-type have all steel gears and heavy duty lubricant for extended lifetime performance.

